



FORCRETE.
EVERY SURFACE MATTERS

MONO SEAL

P 01603 455962

E sales@forcrete.co.uk

W www.forcrete.co.uk

PRODUCT DESCRIPTION

Mono-Seal is a single component, cross linking, polyurethane sealer which forms part of the Trowel-X system.

Must only be used when the 'Diamond Polished' finish has been selected.

MATERIAL FEATURES

- Matt Finish
- Single Component
- Water vapor diffusion capable
- Touch dry in 1-2 hours
- Can be forced dried

KEY INFORMATION



USE NEAT



TECHNICAL DATA

Product type: Sealer

Appearance: White liquid

Chemical Nature: Polyurethane

Shelf Life: 12 months

Consumption = 120g–150g per m²

User Time – Unlimited

MONO SEAL APPLICATION INSTRUCTIONS

1. SURFACE PREPARATION

The substrate must be firm, dimensionally stable, capable of bearing loads and free of loose constituents, dust, oil, grease, rubber marks and other substances that could interfere with adhesion.

2. APPLICATION

Using a 12inch microfibre roller apply in a cross-hatch technique ensuing roller lines are minimised.

A layer of Trowel-X Liquid Wax or Forcrete Renovator should be applied on top as a sacrificial layer for additional protection.

Consumption rate: 120g – 150g /m²

3. SPECIAL PRECAUTIONS

- For professional use only
 - Do not apply below +5c or above +25c
 - Keep out of reach of children
 - Dispose of waste in accordance with current legislation
-

4. CLEANING OF TOOLS

Clean tools, equipment, and any splashed material immediately with water while still fresh. Take suitable protective and waste disposal measures when cleaning.