

DECORWAX



Description of product

Aqueous-base wax for Venetian stucco and marmorino.

Application Field

Protection and conservation for prestigious decorative finishing.

Product characteristics

The composition of DECORWAX is a synthesis of polymer substances and natural derivatives carefully emulsified that makes the product easy to use with a good final brightness. The colour shades can be personalized using the scheme of the Tintometric system Luxury&Lime. Its applications makes the surfaces solid by penetrating into porosities: the surface results more resistant to external aggressives. The treated surfaces will remain stable in time without chromatic alterations.

Technical data	
Name	Decorwax
Composition	Decorative wax, polymer substances and natural derivatives.
Aspect	Liquid
Color	Opalescent White
Dilution	Ready to use
Quantity per layer	approx. 7 - 10 m2/kg
VOC class	VOC 0g/l - wall paint and subcategory "L" max.value UE2010 30g/l
Specific weight	1 kg/litre
Packaging	1 - 5 lt packaging
Storage	Keep in dry place with temperture min.5° - 30°C max.
Notice	Protect the surfaces during the 12 hours after application

DECORWAX

Instructions for use

- Application with sponge, pads, cloths and paintbrush
- Application of 1 or more coats according to needs
- Important that surfaces be solid and stable
- DECORWAX is ready to use but can also be diluted with water, and easily coloured.
- The product can be applied using different tools: sponge, pad, cloth, paintbrush according to the decorative effect to be obtained. Remove with cloth any excess of wax
- After about 30 min. and not more than 2 hours, proceed to polishing with special cloths or using a polishing machine with wool pads
- Protect from rain external decoratives for at least 48 hours
- Temperature of application 5° - 35°C. Do not apply the product in case of imminent rain or windy days

Notes

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

Date of issue 01.04.2004

BeriCalce ITALIA

Via Odorico da Pordenone, 18

36100 Vicenza - ITALY

Phone (+39) 0444 929102

Fax (+39) 0444 929102

Skype: bericalce

info@bericalce.com

bericalce.com