



Suitable for external uses.



The product can be pigmented.

# MICRO-PRIMER VENEZIANO

## VENETIAN MICRO-PRIMER

### Description of product

Micro-granular covering anchor primer to be applied with paintbrush or roller. To be used as generic primer for any kind of decoratives even lime-based products (maximum granulometric 150 micron).

### Application Field

Micro-granular primer for interiors and exteriors.

### Product characteristics

MICRO-PRIMER VENEZIANO is an innovative product, especially studied for surfaces that need a strong anchor primer. Often, the technicians must apply spatolati or marmorini on smooth or treated surfaces: from here the necessity of a product to guarantee a solid and strong anchorage. MICRO-PRIMER VENEZIANO a fine product, composed of high adherence vinyl resins mixed with micro-marble grits sifted at 150micron. Venetian Micro-Primer is dense and once diluted, the thixotropic remains and does not drain; the micro-grits remain homogenously mixed in the paste to obtain an uniform wall application. The final aspect will appear slightly rough and white colour. The colour shades can be personalized using the colour scheme of the Tintometric system Luxury&Lime. Excellent for applications on cement, plaster, bricks, plasterboards and old hydro-paints.

| Technical data     |  |
|--------------------|--|
| Name               | Micro-Primer Veneziano   |
| Composition        | Vinyl resins mixed with powders and micro-marble grits           |
| Aspect             | Dense Paste  |
| Color              | White  |
| Dilution           | In water 10 - 25%  |
| Quantity per layer | approx. 5 - 7 m2/kg  |
| PH                 | 9,5  |
| VOC class          | VOC 5g/l - wall paint and subcategory "L" max.value UE2010 30g/l |
| Specific weight    | 1,58 kg/litre  |
| Packaging          | 5 - 15 lt packaging  |
| Storage            | Keep in dry place with temperture min.5° - 30°C max.             |
| Notice             | Protect the surfaces during the 12 hours after application       |

# **MICRO-PRIMER VENEZIANO**

---

## **Instructions for use**

- Application with paintbrush and roller
- Application of 1 or more coatings
- Base must be clean and dry, any unsubstantial parts, traces of oil or grease must be removed; plaster any irregularity of the base
- In order to keep unvaried the thixotropy of the product and to guarantee adherence, we suggest a dilution of not more than 25%
- On difficult surfaces, we suggest a low dilution
- The product can be applied on many kinds of surfaces (marmorino, grassello, plasterboard, wood panels, etc.) ensuring an excellent adherence and good solid base for further applications
- The product is composed of vinyl resin (30%) with micro-marble grits, therefore does not tarnish if spatolato
- Temperature of application 5° to 35°C

## **Notes**

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

**Date of issue 01.04.2004**

## **BeriCalce ITALIA**

Via Odorico da Pordenone, 18

36100 Vicenza - ITALY

Phone (+39) 0444 929102

Fax (+39) 0444 929102

Skype: bericalce

info@bericalce.com

**bericalce.com**