

L'ACRILICO

UNIVERSAL ACRYLIC PAINT

PRODUCT PROPERTIES

L'ACRILICO is a water based mural paint formulated with acrylic resins in water dispersion, very pure pigments, fine fillers and various high quality additives that grant it the following characteristics:

EXCELLENT HIDING POWER - GOOD BRUSHABILITY - GOOD TRANSPIRABILITY - GOOD WASHABILITY - EASY TO APPLY.

IDEAL USES

L'ACRILICO is ideal to decorate interior masonry walls, plasterboards, masonite ones and any other mural surface in civil buildings.

It is the specific base for the following decoration with CHIC *Classic*, CHIC *Metal*, LE VELATURE, ELITE SETA, OMBRE and CHIFFON.

TECHNICAL CHARACTERISTICS

SPECIFIC WEIGHT:

1,53 - 1,63 kg/l.

VISCOSITY:

15.000 - 20.000 cps (20 rpm, spindle 5) at 20 °C.

SPREAD RATE PER COAT:

10 - 12 m²/l.

It may vary depending on roughness, porosity and absorption of the surface, as well as on the application method adopted.

DRY RESIDUAL:

67% ± 1%.

AVERAGE DRY FILM THICKNESS:

Approximately 60 µ in 2 coats.

WET ABRASION RESISTANCE:

Class 2 washable and brushable wall paint according to EN 13300 and EN ISO 11998.

APPEARANCE AND FINISH:

Matt appearance, smooth finish.

VOC EMISSION LIMITS

(VOLATILE ORGANIC COMPOUNDS):

EU limit value of VOC (Directive 2004/42/EC) for these products (cat. A/a;WB): 75 g/l (2007); 30 g/l (2010).

L'ACRILICO contains a maximum of 30 g/l of VOC.

WAY OF USE

PREPARATION OF THE SURFACE:

ON NEW SURFACES: putty, sandpaper, brush, then apply one coat of PRIMER UNIFORMANTE A.S. properly diluted.

ON ALREADY TREATED SURFACES: remove the semi-detaching parts, then proceed as on new surfaces.

APPLICATION:

L'ACRILICO can be applied by pure bristle brush or wool roller.

DILUTION

First coat: 25-30% in volume of water.

Second coat: 20-25% in volume of water.

DRYING AT 20°C AND 65% R.H.:

By touch 30 - 40 minutes, in depth about 24 hours.

TIME BETWEEN COATS:

Wait at least 3-4 hours.

When used as a base wait at least 24 hours before the following application of the decorative finishing.

ENVIRONMENTAL CONDITIONS:

The product can be applied at temperatures (of both the environment and/or the surface) between +5°C and +30°C.

TOOLS CLEANING:

With water immediately after use.

SALES PACKAGINGS: 2 x 2,5 l - 2 x 5 l - 1 x 15 l.

AVAILABLE COLOURS: White and colours chart.

CONSERVATION AND STORAGE:

Store the cans well sealed in a cool and dry place, far away from frost.

NOTES:

This document has been issued at the best of our technical and scientific expertise. Di Donato Spa does not take any responsibility for the results obtained when using this product, since the conditions and application procedures are not controllable by us. Therefore it is advisable to preliminary check the suitability of the product in accordance with the specific case.

