



The product can be pigmented.

TECHNICAL **CHART 73**

# PURE VARNISH MONO SATIN 30

## Description of product

Water-based polyurethane one-component satin varnish, with a high transparency.

## Application field

Protective finishing on interior walls.

## Product characteristics

PURE VARNISH MONO SATIN 30 protects the treated surfaces forming a uniform satin waterproof film, which has the following characteristics:

- great adherence to the major part of surfaces, if dry and properly treated;
- good resistance to usury;
- good flexibility.

Technical data	
Name	Pure Varnish Mono Satin 30
Composition	Water-based satin resin for interior walls
Aspect	Milky liquid
Color	Transparent
Dilution	Ready to use (eventual dilution in water 5-15%)
Quantity per layer	approx. 4 - 6 m <sup>2</sup> /l
VOC class	VOC 75,15 g/l (max. limit 130)
Specific weight	1,05 g/cm <sup>3</sup>
Packaging	1 - 5 liters packages
Storage	The product remains unchanged for at least one year if kept in a closed and sheltered environment at a temperature between 5 - 35 °C. Protect from frost!
Notice	<ul style="list-style-type: none"> <li>• Mix the product well before use.</li> <li>• Do not dispose of paint residues in the sewers.</li> <li>• The equipment should be washed immediately after use with water.</li> </ul>

# **PURE VARNISH MONO SATIN 30**

---

## **Instructions for use**

- Mix the product well before use.
- In the application phase, both for the product and for the support and the environment, it is preferable that the temperature is not lower than 15 ° C. The films formed below this temperature have chemical and mechanical resistance properties that are lower than the commonly obtainable quality standard.
- Application with roller or spray
- The product is applied in 2 or more coats.
- Apply the next coat after the hardening of the previous one.

## **Note**

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

**Date of issue 01.09.2017**

**Date of update 16.01.2019**

## **BeriCalce ITALIA**

Via Odorico da Pordenone, 18

36100 Vicenza - ITALIA

Tel./Fax (+39) 0444 929102

Tel. (+39) 0444 923317

Skype: bericalce

info@bericalce.com

**bericalce.com**