

STILI DI VERTIGO®

HEAVY TEXTURED COATING FOR INTERIORS AND EXTERIORS USE

PRODUCT PROPERTIES

STILI DI VERTIGO® is an internal coating formulated with resins in aqueous emulsion with marble grains of various sizes and with quality additives that give the product the following characteristics: PLASTICITY - BREATHABILITY - ALKALINE STABILITY - EXCELLENT BONDING TO THE SUBSTRATE. The special formulation allows for easy application of decorative finishes to achieve incredible and diverse aesthetic effects.

STILI DI VERTIGO® can be coloured by the Speedy ColorManager tinting system.

IDEAL USES

STILI DI VERTIGO® can be applied on the inner walls of masonry, plasterboard, cement-based substrates as well as to old organic or mineral based paint and coatings provided they are dry and intact. It is particularly suitable to be finished with CHIC®CLASSIC, CHIC®METAL, CHIC®FINE, CHIFFON®, and TRESOR® products from Di Donato.

TECHNICAL CHARACTERISTICS

SPECIFIC WEIGHT:

1,78 - 1,83 kg/l.

VISCOSITY:

Paste type product.

SPREAD RATE PER COAT:

1 - 1,5 kg/sq m.

It varies according to the condition of the substrate and the thickness applied. It may be necessary to determine the actual yield with a preliminary test on a specific substrate.

VOLUME SOLIDS:

82% ± 1%.

GRAIN SIZE:

< 600 micron.

VOC EMISSION LIMITS (VOLATILE ORGANIC COMPOUNDS):

EU limit value of VOC (Directive 2004/42/EC) for these products (Cat. A/a; WB): 75 g/l (2007); 30 g/l (2010).

STILI DI VERTIGO® contains a maximum of 30 g/l of VOC.

WAY OF USE

SURFACE PREPARATION:

On new surfaces, make sure, that the wall will be completely dry, clean thoroughly removing dust and/or any loose material, then apply a coat of PRIMER UNIFORMANTE AS.

On Painted surfaces, make sure, that the wall will be completely dry, remove any loose material, if necessary, restore with a special mortar and apply a coat of PRIMER UNIFORMANTE AS.

For internal surfaces: after about 6-8 hours apply one coat of FONDO AS with brush or roller.

For external surfaces: after about 6-8 hours apply a coat of smoothing primer SILOGRUND® or ACRILHEX® SILOSSANICO with brush or roller.

APPLICATION: STILI DI VERTIGO® can be applied and patterned with a steel trowel, sea sponge, crescent sponge, hard brush or fan style wire brush.

Apply the product with the most suitable tool in order to obtain one of the 11 STILI DI VERTIGO® visual texture styles or a custom effect, following the standards of contemporary style.

-Style DEVORÉ: Apply an even layer of STILI DI VERTIGO® with the stainless steel trowel. Whilst the product is still wet, create the design using the Fill Posè pad, then the natural sponge to increase the texture, shaping the design with slanting movements. Wait at least 30-45 minutes for the product to dry completely and refine with a slightly moistened stainless steel trowel, ensuring it is always clean. When the STILI DI VERTIGO® is completely dry, apply a coat of CHIC®FINE of the colour chosen using the perlon yellow roller, then spread the product in the same direction as the texture of STILI DI VERTIGO coating using the half-moon sponge.

-Style DENIM: Apply an even layer of STILI DI VERTIGO® with the stainless steel trowel. Whilst the product is still wet, create the design with the Fill Posè pad, using staggered horizontal movements. Wait at least 30-45 minutes for the product to dry completely and refine with a slightly moistened stainless steel trowel, ensuring it is always clean. When the STILI DI VERTIGO® is completely dry, apply a coat of CHIC®FINE of the colour chosen using the perlon yellow roller, then spread the product in the same direction as the texture of STILI DI VERTIGO® coating using the half-moon sponge.

-Style FLAMMÉ: Create a series of vertically-arranged rectangles on the wall with the masking tape and then apply an even layer of STILI DI VERTIGO® with the stainless steel trowel. Whilst the product is still wet, create the design with the Fill Posè pad using staggered vertical movements. Wait at least 30-45 minutes for the product to dry completely and refine with a slightly moistened stainless steel trowel, ensuring it is always clean. When the



STILI DI VERTIGO®

HEAVY TEXTURED COATING FOR INTERIORS AND EXTERIORS USE

STILI DI VERTIGO® is completely dry, apply a coat of CHIC®FINE of the colour chosen using the perlon yellow roller, then spread the product in the same direction as the texture of STILI DI VERTIGO® coating using the half-moon sponge.

-Style LIANE: Apply an even layer of STILI DI VERTIGO® with the stainless steel trowel. Whilst the product is still wet, create the design using the Liane trowel with wavy sides by moving it vertically from top to bottom. Wait at least 30-45 minutes for the product to dry completely and refine with a slightly moistened stainless steel trowel, ensuring it is always clean. When the STILI DI VERTIGO® is completely dry, apply a coat of CHIC®FINE of the colour chosen using the perlon yellow roller, then spread the product in the same direction as the texture of STILI DI VERTIGO® coating using the half-moon sponge.

-Style OTTOMAN: Create a series of rectangles on the wall with the masking tape and then apply an even coat of STILI DI VERTIGO® with the stainless steel trowel. Whilst the product is still wet, create the design with the fine-tooth comb or the notched spatula following staggered vertical and horizontal movements. Wait at least 30-45 minutes for the product to dry completely and refine with a slightly moistened stainless steel trowel, ensuring it is always clean. When the STILI DI VERTIGO® is completely dry, apply a coat of CHIC®FINE of the colour chosen using the perlon yellow roller, then spread the product in the same direction as the texture of STILI DI VERTIGO® coating using the half-moon sponge.

-Style SHANTUNG: Apply an even layer of STILI DI VERTIGO® with the stainless steel trowel. Whilst the product is still wet, create the design by applying a discontinuous and uneven second coat using the same trowel. Wait at least 30-45 minutes for the product to dry completely and refine with a slightly moistened stainless steel trowel, ensuring it is always clean. When the STILI DI VERTIGO® is completely dry, apply a coat of CHIC®FINE of the colour chosen using the perlon yellow roller, then spread the product in the same direction as the texture of STILI DI VERTIGO® coating using the half-moon sponge.

-Style JUTA: Apply an even layer of STILI DI VERTIGO® with the stainless steel trowel. Whilst the product is still wet, create the design using the Fill Posè pad, moving in horizontal and vertical crisscrosses. Wait at least 30-45 minutes for the product to dry completely and refine with a slightly moistened stainless steel trowel, ensuring it is always clean. When the STILI DI VERTIGO® is completely dry, apply a coat of CHIC®FINE of the colour chosen using the perlon yellow roller, then spread the product in the same direction as the texture of STILI DI VERTIGO® coating using the half-moon sponge.

-Style ALCANTARA: Apply an even layer of STILI DI VERTIGO® with the stainless steel trowel. Whilst the product is still wet, create the design using the special

yellow-striped perlon roller, moving in horizontal and vertical crisscrosses. Wait at least 30-45 minutes for the product to dry completely and refine with a slightly moistened stainless steel trowel, ensuring it is always clean. When the STILI DI VERTIGO® is completely dry, apply a coat of CHIC®FINE of the colour chosen using the perlon yellow roller, then spread the product in the same direction as the texture of STILI DI VERTIGO® coating using the half-moon sponge.

-Style NABUK: Apply an even layer of STILI DI VERTIGO® with the stainless steel trowel. Whilst the product is still wet, create the design using the special nabuk-embossed rubber roller in vertical strokes. Wait at least 30-45 minutes for the product to dry completely and refine with a slightly moistened stainless steel trowel, ensuring it is always clean. When the STILI DI VERTIGO® is completely dry, apply a coat of CHIC®FINE of the colour chosen using the perlon yellow roller, then spread the product in the same direction as the texture of STILI DI VERTIGO® coating using the half-moon sponge.

-Style CRÊPE: Apply an even layer of STILI DI VERTIGO® with the stainless steel trowel. Whilst the product is still wet, create the design by blotting the surface in criss-cross movements with the trowel loaded with a small amount of product. Wait at least 30-45 minutes for the product to dry completely and refine with a slightly moistened stainless steel trowel, ensuring it is always clean. When the STILI DI VERTIGO® is completely dry, apply a coat of CHIC®FINE of the colour chosen using the perlon yellow roller, then spread the product in the same direction as the texture of STILI DI VERTIGO® coating using the half-moon sponge.

-Style SPIGATO: Apply an even layer of STILI DI VERTIGO® with the stainless steel trowel. Whilst the product is still wet, create the design with the Fill Posè pad, using staggered vertical movements. Wait at least 30-45 minutes for the product to dry completely and refine with a slightly moistened stainless steel trowel, ensuring it is always clean. When the STILI DI VERTIGO® is completely dry, apply a coat of CHIC®FINE of the colour chosen using the perlon yellow roller, then spread the product in the same direction as the texture of STILI DI VERTIGO® coating using the half-moon sponge.

DRYING AT 20°C AND 65% R.H:

Touch dry after 5-6 hours, completely dry in approximately 24 hours.

TIME BETWEEN COATS:

STILI DI VERTIGO® can be painted over after approximately 24 hours at +20°C.

DILUTION:

The product is ready for use. If necessary it can be diluted with a maximum of 2% water.



STILI DI VERTIGO®

HEAVY TEXTURED COATING FOR INTERIORS AND EXTERIORS USE

ENVIRONMENTAL CONDITIONS:

Apply the product when the temperature of both the general environment and the supports between +5°C and +30°C.

WARNINGS:

It is recommended to apply the product in favorable climatic conditions as indicated above. The application of the product in unsuitable atmospheric conditions negatively affects drying times, compromising the optimal achievement of aesthetic and performance characteristics. Not dried plasters can cause discolouring, streaks and the formation of salt efflorescence. After application, protect the surfaces from rain and humidity for about 48 hours until the product is completely dry.

TOOLS CLEANING:

With water immediately after use.

SALES PACKAGINGS:

8 kg – 24 kg.

AVAILABLE COLOURS:

White. STILI DI VERTIGO® can be colored using the Speedy ColorManager S2K tinting system.

CONSERVATION AND STORAGE:

The product will remain in good condition for at least 18 months if stored in a cool, dry frost free place.

NOTE:

This document has been prepared to the best of our scientific and technical knowledge.

Di Donato SpA does not assume any responsibility for the results obtained when using this product as the conditions and methods of application are various and are not controlled by us.

We therefore advise that for best results the product is pre-tested to assess its suitability for individual specific cases.

