

FINITURA TRASPARENTE PROTETTIVA

PRODUCT PROPERTIES

FINITURA TRASPARENTE PROTETTIVA is a product based on unsaponifiable acrylic resins and special additives. Its main function is to consolidate the surface, enhancing the wet abrasion resistance. The product is transparent and thus do not affect the final aesthetic result of the treated surface.

IDEAL USES

FINITURA TRASPARENTE PROTETTIVA is suitable to grant a further protection to all Antica Signoria decorative finishings, especially to DAMASCATO STELLARE.

TECHNICAL CHARACTERISTICS

SPECIFIC WEIGHT:

0,98 1,02 kg/l.

SPREAD RATE PER COAT:

Approximately 6 m²/l.

It is recommended to preliminary check the absorption of the surface.

VOC EMISSION LIMITS

(VOLATILE ORGANIC COMPOUNDS):

EU limit value of VOC (Directive 2004/42/EC) for these products (Cat. A/g;WB): 50 g/l (2007) ; 30 g/l (2010).

FINITURA TRASPARENTE PROTETTIVA contains a maximum of 30 g/l of VOC.

WAY OF USE

APPLICATION:

By pure bristle brush or wool roller.

DILUTION:

Ready to use product.

DRYING AT 20°C AND 65% R.H.:

By touch 60-90 minutes, in depth about 24 hours.

ENVIRONMENTAL CONDITIONS:

The product can be applied at temperatures (of both the environment and/or the surface) between +5°C and +30°C.

TOOLS CLEANING:

With water immediately after use.

SALES PACKAGINGS: 12 x 1 l.

AVAILABLE COLOURS: Transparent.

CONSERVATION AND STORAGE:

Store the cans in a cool place, far away from frost.

NOTES:

This document has been issued at the best of our technical and scientific expertise. Di Donato Spa does not take any responsibility for the results obtained when using this product, since the conditions and application procedures are not controllable by us. Therefore it is advisable to preliminary check the suitability of the product in accordance with the specific case.

