

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name TROWEL-X BASE Comp B.

Date of issue: 10/11/2025

Date of revision: 11/11/2028

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name TROWEL-X BASE, Comp. B

Article number: 202031.02

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Australian Importer / Supplier:

Name: Calce Company Pty Ltd

Address: 24/13-15 Baker Street, Banksmeadow NSW 2019, Australia

Telephone: +61 2 9666 4492

Email: info@calcecompany.com

Manufacturer

Forcrete Ltd

6 Fitzmaurice Court Industrial Estate, Valley Side, Wymondham NR18 0NN

Tel: +441603455962

Mob: +447472483348

Information department:

Product Safety department: George Hunt Tel: +447472483348

E-Mail: sales@forcrete.co.uk

1.4 Emergency telephone number:

Emergency Services (Australia): 000

Poisons Information Centre (Australia): 13 11 26 (24 hours / 7 days)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Safety data sheet

according to 1907/2006/EC, Article 31

Date of issue: 10/11/2025

Date of revision: 11/11/2028

Trade name TROWEL-X BASE Comp B.

Hazard pictograms



Signal word Warning

Hazard-determining components of labelling:

bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700)

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

hexandiol diglycidylether

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

The residual content of epichlorhydrin corresponds to APME recommendations: modified resins < 10 ppm (0.001%)

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Safety data sheet

according to 1907/2006/EC, Article 31

Date of issue: 10/11/2025

Trade name TROWEL-X BASE Comp B.

Date of revision: 11/11/2028

Description: Mixture of the substances listed below with harmless additions.

Dangerous components:		
CAS: 28064-14-4 NLP: 500-006-8 Reg.nr.: 01-2119454392-40-XXXX	bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥40-<60%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥25-<40%
CAS: 16096-31-4 EINECS: 240-260-4 Reg.nr.: 01-2119463471-41-XXXX	hexandiol diglycidylether Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥10-<20%
CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0 Reg.nr.: 01-2119475108-36-XXXX	2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≥10-<20%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information When symptoms occur or in case of doubt, seek medical advice

After inhalation Take affected persons into the open air and position comfortably

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact If skin irritation continues, consult a doctor.

After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Carbon monoxide (CO)

Safety data sheet

according to 1907/2006/EC, Article 31

Date of issue: 10/11/2025

Trade name TROWEL-X BASE Comp B.

Date of revision: 11/11/2028

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen chloride (HCl)

5.3 Advice for firefighters

Protective equipment: Wear self-contained breathing apparatus.

Wear full protective suit.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated firefighting water separately. It must not enter drains.

Dispose of fire debris and contaminated firefighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

Dilute with plenty of water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Use neutralising agent.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: No special requirements.

Safety data sheet

according to 1907/2006/EC, Article 31

Date of issue: 10/11/2025

Trade name TROWEL-X BASE Comp B.

Date of revision: 11/11/2028

Information on storage in a common storage facility: Store away from oxidising agents.

Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

7.3 Specific end use(s) No further relevant information available

SECTION 8: Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

CAS: 111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm

Long-term value: 123 mg/m³, 25 ppm

Sk, BMGV

Ingredients with biological limit values:

CAS: 111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: butoxyacetic acid

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective equipment is not required, or the amount of the PPE can be adapted accordingly.

Respiratory equipment:

Safety data sheet

according to 1907/2006/EC, Article 31

Date of issue: 10/11/2025

Date of revision: 11/11/2028

Trade name TROWEL-X BASE Comp B.

Respiratory protection recommended.

Filter A/P2.

Only use ambient air independent respiratory equipment in pits, shafts and silos.

Protection of hands:

Long cuffed gloves

Protective gloves.

The glove material must be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore, a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time must be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid

Colour: Clear

Odour: Weak, Characteristic

Odour threshold: Not determined.

pH-value: Not determined.

Change in condition

Melting point/freezing point: Not determined

Initial boiling point and boiling range: >105°C

Flash point: ca. 84°C

Inflammability (solid, gaseous) Not applicable.

Ignition temperature: Not applicable.

Decomposition temperature: Not applicable.

Safety data sheet

according to 1907/2006/EC, Article 31

Date of issue: 10/11/2025

Trade name TROWEL-X BASE Comp B.

Date of revision: 11/11/2028

Self-inflammability: Product is not self-igniting.
Explosive properties: Product is not explosive.
Explosive Limits: Lower: Not determined. Upper: Not determined.
Vapour pressure at 20°C: Not determined.
Density at 20 °C: ca. 1.11 g/cm ³ Relative density: Not determined. Vapour density: Not determined. Evaporation rate: Not determined.
Solubility in / Miscibility with Water: fully miscible
Distribution coefficient (n-octanol/water): Not determined.
Viscosity: Dynamic at 20°C: 200 mPas Kinematic: Not determined.
Solvent separation test: < 3%
Organic solvents: 10.5 %
9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions Danger of bursting

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: Acids

10.6 Hazardous decomposition products:

None if used properly.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral LD50 >10,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

CAS: 16096-31-4 hexandiol diglycidylether

Oral LD50 2,900 mg/kg (rat)

Dermal LD50 >4,900 mg/kg (rat)

CAS: 111-76-2 2-butoxyethanol

Oral LD50 1,480 mg/kg (rat)

Safety data sheet

according to 1907/2006/EC, Article 31

Date of issue: 10/11/2025

Date of revision: 11/11/2028

Trade name TROWEL-X BASE Comp B.

Dermal LD50 2,000 mg/kg (guinea pig)

<2,000 mg/kg (rabbit)

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation

Sensitisation: May cause an allergic skin reaction.

Experience with humans: Frequent or longer lasting skin contact may degrease and dry out skin which may lead to skin irritation and inflammation (dermatitis).

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations.

Hardened product remains may be disposed of as building rubble or put into household garbage.

according to 1907/2006/EC, Article 31

Date of revision: 11/11/2028

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

08 01 11*- waste paint and varnish containing organic solvents or other hazardous substances

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent: Water, if necessary with cleaning agent.

14.1 UN-Number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR IMDG IATA	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700), Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700))) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight
14.3 Transport hazard class(es) ADR Class Label IMDG, IATA Class Label	 9 (M6) Miscellaneous hazardous substances and articles. 9 9 (M6) Miscellaneous hazardous substances and articles. 9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant: Special marking (ADR):	mp Yes Symbol (fish and tree) Symbol (fish and tree)

Safety data sheet

according to 1907/2006/EC, Article 31

Date of issue: 10/11/2025

Date of revision: 11/11/2028

Trade name TROWEL-X BASE Comp B.

Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user hazard identification number: EMS Number: Stowage Category	Warning: Miscellaneous hazardous substances and articles. 90 F-A,S-F A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Code: E1 Transport category IMDG Limited quantities (LQ) Excepted quantities (EQ)	Not applicable. 5L Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN(NUMBER AVERAGE MOLECULAR WEIGHT<700), EPOXY RESIN (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN) (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700))), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

Safety data sheet

according to 1907/2006/EC, Article 31

Date of issue: 10/11/2025

Date of revision: 11/11/2028

Trade name TROWEL-X BASE Comp B.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3