

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM CA.

Date of Issue: 20/11/2025

Date of Revision: 14/12/2028

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name FORPRIME-DPM, CA

Article number: 20203.01

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Australian Importer / Supplier:

Name: Calce Company Pty Ltd

Address: 24/13-15 Baker Street, Banksmeadow NSW 2019, Australia

Telephone: +61 2 9666 4492

Email: info@calcecompany.com

Manufacturer

Forcrete Ltd

6 Fitzmaurice Court Industrial Estate, Valley Side, Wymondham NR18 0NN

Tel: +441603455962

Mob: +447472483348

Information department:

Product Safety department: George Hunt Tel: +447472483348

E-Mail: sales@forcrete.co.uk

1.4 Emergency telephone number:

Emergency Services (Australia): 000

Poisons Information Centre (Australia): 13 11 26 (24 hours / 7 days)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Safety data sheet

according to 1907/2006/EC, Article 31

Date of Issue: 20/11/2025


Trade name **FORPRIME-DPM CA.**

Date of Revision: 14/12/2028

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



Signal word Warning

Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700)

bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700)

[[2-ethylhexyl)oxy]methyl]oxirane

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures Description: Mixture of the substances listed below with harmless additions.

Safety data sheet

according to 1907/2006/EC, Article 31

Date of Issue: 20/11/2025

Trade name FORPRIME-DPM CA.

Date of Revision: 14/12/2028

Dangerous components [% w/w]:		
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	72%
CAS: 28064-14-4 NLP: 500-006-8 Reg.nr.: 01-2119454392-40-XXXX	bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	16%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-XXXX	benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	10%
CAS: 2461-15-6 EINECS: 219-553-6 Reg.nr.: 01-2119962196-31-XXXX	[[2-ethylhexyl]oxy]methyl]oxirane Skin Irrit. 2, H315; Skin Sens. 1, H317	2%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation

Use a respiration bag or breathing device.

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact Wash immediately with water and soap and rinse thoroughly.

After eye contact Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Water spray jet

Carbon dioxide

Foam

Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Safety data sheet

according to 1907/2006/EC, Article 31

Date of Issue: 20/11/2025

Trade name **FORPRIME-DPM CA.**

Date of Revision: 14/12/2028

Hydrogen chloride (HCl)

further harmful conflagration gases and fumes

5.3 Advice for firefighters

Protective equipment: Wear self-contained breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.

Information about protection against explosions and fires: No special requirements.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: Prevent any penetration into the ground.

Information on storage in a common storage facility:

Store away from oxidising.

Store away from food.

Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

7.3 Specific end use(s) No further relevant information available.

Safety data sheet

according to 1907/2006/EC, Article 31

Date of Issue: 20/11/2025

Trade name FORPRIME-DPM CA.

Date of Revision: 14/12/2028

SECTION 8: Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

Respiratory equipment:

Filter A (brown)

Only use ambient air independent respiratory equipment in pits, shafts and silos!

Protection of hands:

Long cuffed gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to

be checked prior to the application.

Penetration time of glove material

Safety data sheet

according to 1907/2006/EC, Article 31

Date of Issue: 20/11/2025

Trade name FORPRIME-DPM CA.

Date of Revision: 14/12/2028

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed safety glasses.

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
General Information
Appearance:
Form: Fluid
Colour: clear
Odour: Weak, characteristic
Odour threshold: Not determined.
pH-value: Not determined.
Change in condition
Melting point/freezing point: Not determined
Initial boiling point and boiling range: >100 °C
Flash point: >100 °C
Inflammability (solid, gaseous) Not applicable.
Ignition temperature: not applicable
Decomposition temperature: Not determined.
Self-inflammability: Product is not self-igniting.
Explosive properties: Product is not explosive.
Explosive Limits:
Lower: Not determined.
Upper: Not determined.
Vapour pressure: Not determined.
Density at 20 °C: 1.15-1.16 g/cm ³
Relative density Not determined.
Vapour density Not determined.
Evaporation rate Not determined.
Solubility in / Miscibility with
Water: Not miscible or difficult to mix
Distribution coefficient (n-octanol/water): Not determined.
Viscosity:
dynamic at 20 °C: 900-950 mPas
kinematic: Not determined.
Solvent separation test < 3 %
9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

Safety data sheet

according to 1907/2006/EC, Article 31

Date of Issue: 20/11/2025

Trade name FORPRIME-DPM CA.

Date of Revision: 14/12/2028

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions Exothermic polymerisation

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

May be released in fire:

Carbon monoxide and carbon dioxide

Hydrogen chloride (HCl)

Phenol

SECTION 11: Toxicological information

11.1 Information on toxicological effects Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral LD50 >10,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Sensitisation:

May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

Safety data sheet

according to 1907/2006/EC, Article 31

Date of Issue: 20/11/2025

Trade name FORPRIME-DPM CA.

Date of Revision: 14/12/2028

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark: Toxic for fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations.

Hardened product remains may be disposed of as building rubble or put into household garbage.

The given refuse codes are recommendations based upon the intended use of the product. Because of

special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

20 01 28 paint, inks, adhesives and resins other than those mentioned in 20 01 27

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

* SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA UN3082

14.2 UN proper shipping name

ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight $\leq$ 700)))
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight $\leq$ 700))), MARINE POLLUTANT

Safety data sheet

according to 1907/2006/EC, Article 31

Date of Issue: 20/11/2025

Trade name FORPRIME-DPM CA.

Date of Revision: 14/12/2028

IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700)))
14.3 Transport hazard class(es) ADR   Class Label IMDG, IATA   Class Label	9 (M6) Miscellaneous hazardous substances and articles. 9 9 Miscellaneous hazardous substances and articles. 9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances: Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700))
Marine pollutant: Special marking (ADR): Special marking (IATA):	Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user hazard identification number: EMS Number: Stowage Category	Warning: Miscellaneous hazardous substances and articles. 90 F-A,S-F A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Maximum net quantity per inner packaging: Maximum net quantity per outer packaging: Transport category	5L Code: E1 30 ml 1000 ml 3
IMDG	

Safety data sheet

according to 1907/2006/EC, Article 31

Date of Issue: 20/11/2025

Trade name FORPRIME-DPM CA.

Date of Revision: 14/12/2028

Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (REACTION PRODUCT: BISPHENOL A- (EPICHLORHYDRIN) (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700))), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for

any specific product features and does not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

Safety data sheet

according to 1907/2006/EC, Article 31

Date of Issue: 20/11/2025

Trade name FORPRIME-DPM CA.

Date of Revision: 14/12/2028

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2