



The product can be pigmented.

TECHNICAL **CHART 72**

PURE VARNISH MONO MATT 05

Description of product

Water-based acril polyurethane one-component matt varnish, with a high transparency.

Application field

Protective finishing on interior walls.

Product characteristics

PURE VARNISH MONO MATT 05 protects the treated surfaces forming a uniform matt waterproof film, which has the following characteristics:

- great adherence to the major part of surfaces, if dry and properly treated;
- good resistance to usury;
- good flexibility.

Technical data

Name	Pure Varnish Mono Matt 05
Composition	Water-based matt resin for interior walls
Aspect	Milky liquid
Color	Transparent
Dilution	Ready to use (eventual dilution in water 5-15%)
Quantity per layer	approx. 4 - 6 m ² /l
VOC class	VOC 75,15 g/l (max. limit 130)
Specific weight	1,05 g/cm ³
Packaging	1 - 5 liters packages
Storage	The product remains unchanged for at least one year if kept in a closed and sheltered environment at a temperature between 5 - 35 °C. Protect from frost!
Notice	<ul style="list-style-type: none"> • Mix the product well before use. • Do not dispose of paint residues in the sewers. • The equipment should be washed immediately after use with water.

PURE VARNISH MONO MATT 05

Instructions for use

- Mix the product well before use.
- In the application phase, both for the product and for the support and the environment, it is preferable that the temperature is not lower than 15 ° C. The films formed below this temperature have chemical and mechanical resistance properties that are lower than the commonly obtainable quality standard.
- Application with roller or spray
- The product is applied in 2 or more coats.
- Apply the next coat after the hardening of the previous one.

Note

The present technical chart has been written by Bericalce's experts and the indicated technical and scientific information have been tested in our own workshop.

Any responsibility regarding the results are due only to the method and conditions used during application of the product.

These indications are a valid support for testing the quality of the product in each specific case.

Date of issue 01.09.2017

Date of update 16.01.2019

BeriCalce ITALIA

Via Odorico da Pordenone, 18

36100 Vicenza - ITALIA

Tel./Fax (+39) 0444 929102

Tel. (+39) 0444 923317

Skype: bericalce

info@bericalce.com

bericalce.com