

## ELITE VENEZIA

### TROWEL DECORATIVE FINISHING

#### PRODUCT PROPERTIES

---

ELITE VENEZIA is a product made of synthetic binder, inorganic pigments, calcium carbonate, firming agents, distressing agents, bactericidal and good quality additives that grant to the product the following characteristics: MARBLE LIKE GLOSS FINISH, LOW DIRTY RETENTION, REMARKABLE CHROMATIC EFFECT.

#### IDEAL USES

---

ELITE VENEZIA is the suitable finishing to enrich interior walls of both old and modern buildings.

#### TECHNICAL CHARACTERISTICS

---

**SPECIFIC WEIGHT:**

1,65 - 1,75 kg/l.

**VISCOSITY:**

Paste type product.

**SPREAD RATE PER COAT:**

0,8 - 1 kg/m<sup>2</sup> in 2 coats.

**APPEARANCE AND FINISH:**

Gloss appearance, smooth finish.

**VOC EMISSION LIMITS**

**(VOLATILE ORGANIC COMPOUNDS):**

EU limit value of VOC (Directive 2004/42/CE) for this product (Cat. A/I ; WB): 300 g/l (2007) ; 200 g/l (2010).

ELITE VENEZIA contains less than 200 g/l of VOC.

#### WAY OF USE

---

**ON NEW WALLS:** make sure that the wall has been dried enough and seasoned (28 days at least), and apply one coat of PRIMER UNIFORMANTE A.S. properly diluted.

**ON CRUMBLING or DAMAGED WALLS:** remove all damaged or detached parts, fix with the suitable mortar and then proceed as on new walls.

**ON ALREADY PAINTED WALLS:** remove the old paints, do touch-ups and putty, then proceed as on new walls.

**APPLICATION:**

Apply a first coat of ELITE VENEZIA with stainless steel trowel to make the surface smooth and compact, remove with a thin sandpaper all the possible smears due to the application.

Once obtained an uniform surface proceed to decorate with a steel spatula, by making an irregular spatula finish on the entire surface horizontally and vertically and then remove the exceeding product in the opposite way as for the first coat using the same tool.

Repeat such application until obtaining a total covering of the surface and in order to overlap the coats.

For gloss finish, smooth with the steel trowel (inclined at 45°) applying a slight pressure.

**DILUTION:**

Ready to use product.

**DRYING AT 20°C AND 65% R.H.:**

By touch about 2-3 hours, in depth about 24 hours.

**ENVIRONMENTAL CONDITIONS:**

The product can be applied at temperatures (of both the environment and/or the surface) between +8°C and +30°C.

**TOOLS CLEANING:**

With water immediately after use.

---

**SALES PACKAGINGS:**

1 x 24 kg - 2 x 8 kg - 2 x 4 kg .

**AVAILABLE COLOURS:**

White and colours chart.

**CONSERVATION AND STORAGE:**

Store the cans well sealed in a cool and dry place, far away from frost.

---

**NOTES:**

This document has been issued at the best of our technical and scientific expertise. Di Donato Spa does not take any responsibility for the results obtained when using this product, since the conditions and application procedures are not controllable by us. Therefore it is advisable to preliminary check the suitability of the product in accordance with the specific case.

