

## TECHNICAL DATA SHEET

N. 131.0100

131.0200

Edition 00

www.anticasignoria.it

# CHIC *Heritage*

## INTERIOR TEXTURED FINISH WITH A SANDBLAST EFFECT

### PRODUCT PROPERTIES

---

CHIC *Heritage* is an interior decorative finish with a sandblast effect obtained by combining special resins, selected pigments and special additives in aqueous solution that give the product the following characteristics: HIGH TRANSPIRABILITY - GOOD ADHESION TO THE SUPPORT - EASY TO APPLY - GOOD WASHABILITY RESISTANCE TO ANY CLEANERS - EXCELLENT FILLER ABLE TO SMOOTH OUT ANY IMPERFECTIONS ON THE SUPPORT.

### IDEAL USES

---

CHIC *Heritage* is an interior decorative finish in which pearl like grains with different refraction indexes are incorporated within the media to obtain a reliable aesthetic effect. The versatility of this product makes it ideal for use in both classic and modern environments.

### TECHNICAL CHARACTERISTICS

---

#### SPECIFIC WEIGHT:

1,18 - 1,23 kg/l.

#### VISCOSITY:

8000 - 10000 Cps (brookfield, spindle 5, speed 20 rpm).

#### SPREAD RATE PER COAT:

5 - 6 m<sup>2</sup>/l.

It may vary depending on roughness, porosity and absorption of the surface, as well as on the application method adopted.

#### DRY RESIDUAL:

41% ± 1%.

#### APPEARANCE AND FINISH:

Semi-gloss/matt appearance, finish coarse to the touch.

#### VOC EMISSIONS LIMITS

##### (VOLATILE ORGANIC COMPOUNDS):

EU limit value of VOC (Directive 2004/42/EC) for these products (Cat. A/I ; WB): 300 g/l (2007) ; 200 g/l (2010).

CHIC *Heritage* contains less than 200 g/l of VOC.

### HOW TO USE

---

#### SURFACE PREPARAZION:

ON NEW SURFACES: apply a coat of PRIMER UNIFORMANTE A.S. properly diluted. After 3-4 hours apply one coat of Pittura Acrilica Universale L'ACRILICO.

ON ALREADY PAINTED SURFACES: before applying CHIC *Heritage* finish it is recommended to remove all loose material and oil and/or grease and then to proceed as for new surfaces.

#### APPLICATION:

CHIC *Heritage* can be applied with pure bristle brush, pad, glove or sponge.

The final appearance can be customized by the craftsman depending on the method of application.

A special effect is achieved by applying the product with a brush in one or both hands and crossing the brush strokes.

#### DILUTION:

Ready to use product. If necessary dilute with a maximum of 5% in volume of water.

#### DRYING AT 20°C AND 65% R.H.:

Touch dry after about 2 hours , totally dry after about 24 hours but in order for the product to reach maximum cleaning resistance, wait at least 15 days.

#### TIME BETWEEN COATS:

Approximately 4 hours at 20° C.

#### ENVIRONMENTAL CONDITIONS:

The product must be applied when the temperature of both the environment and/or the surface is between +5°C and +30°C.

#### CLEANING UP:

With water immediately after use.

#### PACK SIZES:

6 x 1,25 - 2 x 2,5L - 2 x 5L - 15L.

#### AVAILABLE COLOURS: Silver, Gold.

The bases can be coloured with Toners or with the Tintometric System Speedy2.

#### CONSERVATION AND STORAGE:

Store the cans well sealed, in a cool and dry place far away from frost.

#### NOTE:

This document has been issued at the best of our technical and scientific expertise. Di Donato Spa does not take any responsibility for the results obtained when using this product, since the conditions and application procedures are not controllable by us. Therefore it is advisable to preliminary check the suitability of the product in accordance with the specific case.



**Antica Signoria**  
MATERIE DECORATIVE